



Xenon Beacons are a cost effective compliment to audible alarms, for use in areas of high ambient noise. The wide operating voltage and automatic synchronisation of the Solex make them a universal solution for all types of alarm and monitoring systems.

- WIDE OPERATING VOLTAGE UP TO 60Vdc
- CURRENT SURGE SUPPRESSION
- AUTOMATIC SYNCHRONISATION
- HIGH EFFICIENCY
- CONSTANT PERFORMANCE OVER VOLTAGE RANGE
- LOCKABLE BASE
- TAMPER SWITCH FOR SECURITY APPLICATIONS
- FIVE LENS COLOURS
- 3 LIGHT OUTPUT OPTIONS
- DEEP BASE / U BASE SUITABLE FOR OUTDOOR USE

## Specification

Voltage	9 - 60Vdc (*1)
Current	Solex 3 85 - 25mA Solex 10 185 - 45mA Solex 15 510 - 120mA (current drops at higher voltage)
Light output	Solex 3 2.5cd Solex 10 10cd Solex 15 15cd
Monitoring	Reverse polarity
Temperature	- 10°C to + 55°C - 25°C to + 70°C
Protection	IP54 (s)* IP65 (d)*
Construction Base	ABS, PC lens
Weight	0.15Kg (s)* 0.18Kg(d)*
Colour	Red or white base
Lens colour	Red, amber, blue, green or clear

(\*1) Solex 3 & 10 will operate from 110 / 230Vac when used with a Deep powered base.

(s)\* Shallow Base

(d)\* Deep / U Base