

The Flashni is an audible and visual device which requires one single installation point. This greatly reduces installation costs and is less obtrusive than two separate devices. Versions are available with the sounder and beacon linked, or with separate terminals for independent operation.


### **Features**


- High output sounder beacon
- 12V, 24V and mains module option
- Choice of lens colour options
- Automatic sounder synchronisation

#### **Benefits**

- Up to 103dB(A) with built in Xenon flash
- Suitable for a variety of application
- Improved tone clarity, reducing confusion

### **Dimensions**





## **Technical Specification**

9 - 15Vdc (12V version)
18 - 28Vdc (24V version) (*1)
110mA 12V version (Typical Tone 5) 68mA 24V version (Typical Tone 3)
103dB(A) 12V version (Typical Tone 5 ) 101dB(A) 24V version (Typical Tone 3)
Pre-set to tone 5 (12v) Pre-set to tone 3 (24v) (versions are available with user selectable tones)
0.7j
1Hz
10dB
Reverse polarity
- 10°C to + 55°C
IP54 (s)* IP65 (d)*
ABS, PC lens
0.33Kg
Red or white
Red, amber, blue, green or clear

Flashni White



# **Catalogue Numbers**

Reference	Cat No	Description
FL/RL/R/S SWITCH	640025FULL-0061X	Flashni Sounder/Beacon, Red lens, Red body, Shallow base, Tone select switch
FL/RL/R/D SWITCH	640031FULL-0111X	Flashni Sounder/Beacon, Red lens, Red body, Deep base, Tone select switch
FL/AL/W/D SWITCH	640024FULL-0060X	Flashni Sounder/Beacon, Amber Iens, White body, Deep base, Tone select switch
FL/RL/R/S 12V SND5	640204FULL-0067	Flashni 12V Sounder/Beacon, Red lens, Red body, Shallow base, tone 5
FL/RL/W/S 12V SND5	640202FULL-0039	Flashni 12V Sounder/Beacon, Red Iens, White body, Shallow base, tone 5
FL/CL/W/S 12V SND5	640206FULL-0089	Flashni 12V Sounder/Beacon, Clear Iens, White body, Shallow base, tone 5